Technical Specifications and Trial Directives of Chain saw (Battery operated)

SNo.	Technical Specifications	Trial Directives
1.	Battery Capacity Min 40 V	BOO to check and verify the parameter through OEM certificate.
2.	Guide Bar Length Min 16” (400 mm)	BOO to physically check and verify the parameter through OEM certificate.
3.	Chain Saw Speed Min 0-5000 fpm	BOO to check and verify the parameter through OEM certificate.
4.	Weight Max 6 Kgs	BOO to physically check and verify the parameter.
5.	Low noise level at only 104 dB(A) with zero emissions for operator comfort and reduced environmental impact	BOO to check and verify the parameter through OEM certificate.
6.	Tool less bar mounting and chain tension adjustment for quick and easy set up and adjustment on the jobsite	BOO to check and verify the parameter through OEM certificate.
7.	Automatic chain oiler maintains optimal bar/chain lubrication during operation with no adjustments required	BOO to check and verify the parameter through OEM certificate.
8.	Chain oil view window enables operator to easily check oil level	BOO to check and verify the parameter through OEM certificate.
9.	Push-button on/off switch with auto power-off function for extended battery life	BOO to check and verify the parameter through OEM certificate.
10.	Lock-off button prevents accidental start up for maximum operator safety	BOO to check and verify the parameter through OEM certificate.
11.	Variable speed trigger switch (0 - 5,020 FPM)	BOO to check and verify the parameter through OEM certificate.
12.	Inertia chain brake provides maximum operator protection if kickback occurs	BOO to check and verify the parameter through OEM certificate.
13.	Wet guard with IPX4 rating offers maximum protection in wet environment.	BOO to check and verify the parameter through OEM certificate.
14.	Ergonomic soft rubber grip design for vibration absorption and comfortable operation	BOO to check and verify the parameter through OEM certificate.